

# TECHNICAL DATA SHEET

## Compact Line 10 & 20

The COMPACT line is the most compact ozone generators on the market for this output. The Compact 10 & 20 are all-in-one ozone generators, with build-in compressor and oxygen-concentrator unit.

|                                     | Compact 10                                    | Compact 20 |
|-------------------------------------|---|------------|
| Ozone concentration output*         | 10 g/h  | 20 g/h     |
| Flow                                | 2 LPM   | 3 LPM      |
| Energy consumption                  | 490 W   | 600 W      |
| Ozone generator technic             | Corona discharge with ceramic                 |            |
| Ozone output                        | PTFE tube connector Ø 6 mm (max 50m)          |            |
| Max distance Compact unit-injection | 50m   |            |
| External connections                | Capacity, alarm, start/stop and safety sensor |            |
| Capacity control                    | 50%/100% or Regulator 0-100% in option        |            |
| Mounting                            | Wall fixture                                  |            |
| Dimensions (HxWxD)                  | 560 x 420 x 220 mm                            |            |
| Weight                              | 23 kg   |            |
| Operation condition                 | +5° to + 30 ° C (optim. 15° C) - <50% rH      |            |
| Supply Voltage                      | 230 V / 50 Hz                                 |            |
| Cover                               | Plastic                                       |            |
| Warranty**                          | 1 year limited warranty                       |            |

\* Relative to ambient conditions. All technical changes and upgrades are reserved INFUSER

\*\*Technical changes reserved

